

DS-65D6N-NLT
65-inch Interactive Flat Panel



□ Specification

Product Model	
Product Model	DS-65D6N-NLT
Panel	
Glass Thickness	3.2 mm
Display	
Screen Size	65 inch
Backlight	DLED
Pixel Pitch	0.124 (H) × 0.372 (V) mm
Resolution	3840 × 2160 @60 Hz
Brightness	400 cd/m ² (Typ.)
Color Depth	10 bit 6 ms 72% NTSC 60 Hz
Response Time	178°(H)/178°(V)
Color Gamut	50000 hours
Refresh Rate	16 : 9 25%Haze
Viewing Angle	
Lifespan	
Aspect Ratio	
Surface Haze	
Touch	
Type	Infrared Touch Screen
Touch Point	40 point multi-touch
Touch Response Time	< 10 ms
Touch Precision	± 1 mm (≥ 90% touching area)
Touch Resolution	32768 x 32768
Built-in System	
Operation System	Android 13.0
Memory	4 GB
Built-in Storage	32 GB
CPU	Cortex-A55 x 4 (1.92GHz)
GPU	Mali-G52 MP2 (2EE)
Internal Function	
Loudspeaker	Built-in 2 ×15 W;
Bluetooth	Built-in BLE (Bluetooth Low Energy) module supports Bluetooth 5.1
Interface	
Video & Audio Input	HDMI In (HDMI 2.0) × 2, Audio In × 1
Video & audio output	Audio Out × 1
Control interface	TOUCH-USB 2.0 × 1, RS232 × 1
Network Interface	LAN (100 Mbps) × 2
Data Transmission Interface	WIFI AP&Station
NFC	USB 3.0 × 4, USB 2.0 × 1, Type-C × 1 (Type-C only supports USB 2.0)
	Reader

Power	
Standby Consumption	0.5 W
General	
Power Supply	100 to 240 VAC, 50/60 Hz
Accessory	Wall mount bracket, hook, QSG, touch writing pen x2, packing list, 1.5m power cable (European standard), remote control.
Working Environment	
Working Temperature	0 °C to 40 °C (32 °F to 104°F)
Working Humidity	10%~90% RH

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq