

Dekesi D-7211D

IP Conference Delegate Microphone



Key Highlights

- Built-in **DSP audio processing** & acoustic echo cancellation
- Independent volume control, **5-band Web EQ** & auto AGC
- Web-based backend management & configuration
- Speaker registration, permission control & **speech timer**
- Camera tracking integration for active speaker
- Remote **firmware upgrade** support
- **Voting / polling** function support

The **Dekesi D-7211D** is a professional IP conference delegate microphone featuring built-in DSP audio processing and acoustic echo cancellation. Designed for seamless integration into IP-based conference systems, it supports independent volume control, 5-band EQ, AGC, speaker registration, speech timer, camera tracking, and meeting voting functions. Remote firmware upgrades and an optional 5W anti-feedback speaker make it a versatile choice for any conference environment.

TECHNICAL SPECIFICATIONS

Model	D-7211D	Web Management	Yes (PC / Mobile / Tablet)
Device Type	IP Conference Delegate Microphone	Speaker Registration	Yes
DSP Audio Processing	Built-in	Speech Timer	Yes
Acoustic Echo Cancel	Yes	Speech Permission	Managed via Central System
Equalizer (EQ)	5-Band Web EQ	Voting / Polling	Yes
AGC	Auto Gain Control — Yes	Built-in Speaker	Optional — 5W Anti-feedback
Volume Control	Independent Adjustment	Remote Firmware OTA	Yes
Camera Tracking	Yes	Connection Type	IP (Wired Network)