

# Dekesi D-7211D

## IP Conference Delegate Microphone



### Key Highlights

- Built-in **DSP audio processing** & acoustic echo cancellation
- Independent volume control, **5-band Web EQ** & auto AGC
- Web-based backend management & configuration
- Speaker registration, permission control & **speech timer**
- Camera tracking integration for active speaker
- Remote **firmware upgrade** support
- **Voting / polling** function support

The **Dekesi D-7211D** is a professional IP conference delegate microphone featuring built-in DSP audio processing and acoustic echo cancellation. Designed for seamless integration into IP-based conference systems, it supports independent volume control, 5-band EQ, AGC, speaker registration, speech timer, camera tracking, and meeting voting functions. Remote firmware upgrades and an optional 5W anti-feedback speaker make it a versatile choice for any conference environment.

### TECHNICAL SPECIFICATIONS

<b>Model</b>	D-7211Z	<b>Web Management</b>	Yes (PC / Mobile / Tablet)
<b>Device Type</b>	IP Conference Delegate Microphone	<b>Chairman Priority</b>	Yes — Override Delegate Mics
<b>DSP Audio Processing</b>	Built-in	<b>Speaker Registration</b>	Yes
<b>Acoustic Echo Cancel</b>	Yes	<b>Speech Timer</b>	Yes
<b>Equalizer (EQ)</b>	5-Band EQ	<b>Voting / Polling</b>	Yes
<b>AGC</b>	Auto Gain Control — Yes	<b>Built-in Speaker</b>	Optional — 5W Anti-feedback
<b>Volume Control</b>	Independent Adjustment	<b>Remote Upgrade</b>	Delegate Device OTA Update
<b>Camera Tracking</b>	Yes	<b>Connection Type</b>	IP (Wired Network)