

Dekesi D-7514D

Digital Delegate Gooseneck Conference Microphone



Key Highlights

- **2.8-inch TFT color display** — real-time meeting status monitoring
- High-performance **embedded CPU** — stable long-duration operation
- **LED ring indicator** on gooseneck — clear active/mute status
- Signal interference protection & **short-circuit protection**
- Fast response: **speech activation, mic status sync** with host
- Seamless integration with **Dekesi digital conference system**
- Flexible deployment — boardrooms, government & **enterprise** venues

The **Dekesi D-7514D** is a professional digital delegate gooseneck conference microphone designed for high-stability meeting systems requiring centralized management and intuitive user interaction. Featuring a 2.8-inch TFT color display and a high-performance embedded CPU, it enables fast speech activation, mic status synchronization, and real-time system feedback. Built-in signal interference protection and short-circuit protection ensure reliable long-duration performance. Compatible with the full Dekesi digital conference ecosystem, it suits boardrooms, government chambers, administrative offices, and command centers.

TECHNICAL SPECIFICATIONS

Model	D-7514D	Short-Circuit Protection	Yes
Device Type	Digital Delegate Gooseneck Microphone	Electrical Surge Protect.	Yes
Display	2.8-inch TFT Color Screen	Speech Activation	Direct On-Device Control
Processor	High-Performance Embedded CPU	Mic Status Sync	Real-Time Sync with Host
Status Indicator	LED Ring on Gooseneck Mic	Central Host Control	Yes
Active Status Display	Yes	PC Software Control	Yes
Mute Status Display	Yes	System Compatibility	Dekesi Digital Conference System
Signal Interference Prot.	Yes	Applications	Boardroom, Government, Enterprise, Admin