

Dekesi P-4D300

4-Channel Digital Power Amplifier



Key Highlights

- **4 independent channels** — 300W × 4 @ 8Ω, 600W × 4 @ 4Ω
- **Bridge mode** support — up to 1200W × 2 @ 8Ω output
- Peak power output **2000W × 2** for demanding applications
- **Digital amplifier technology** — high efficiency & low distortion
- Wide-range power supply: **AC 90V – 265V**, 50/60 Hz
- Full audio spectrum response: **20 Hz – 20 kHz**
- Standard **19-inch rack mount, 1U** — compact & space-saving

The **Dekesi P-4D300** is a professional 4-channel digital power amplifier delivering 300W per channel at 8Ω and 600W per channel at 4Ω. With bridge mode support reaching 1200W × 2 and a peak output of 2000W × 2, it is engineered for high-demand audio installations. Its wide-range AC power input (90V–265V), full-spectrum frequency response (20Hz–20kHz), and compact 1U 19-inch rack design make it ideal for conference halls, auditoriums, and professional AV systems.

TECHNICAL SPECIFICATIONS

Model	D-7211Z	Web Management	Yes (PC / Mobile / Tablet)
Device Type	4-Channel Digital Power Amplifier	Chairman Priority	Yes — Override Delegate Mics
DSP Audio Processing	Built-in	Speaker Registration	Yes
Acoustic Echo Cancel	Yes	Speech Timer	Yes
Equalizer (EQ)	5-Band EQ	Voting / Polling	Yes
AGC	Auto Gain Control — Yes	Built-in Speaker	Optional — 5W Anti-feedback
Volume Control	Independent Adjustment	Remote Upgrade	Delegate Device OTA Update
Camera Tracking	Yes	Connection Type	IP (Wired Network)