

Dekesi D-302YL

35W Compact Column Speaker — 2 × 3-inch Driver



Key Highlights

- Rated power **35W**, impedance **4Ω** — reliable output for mid-size spaces
- **2 × 3-inch drivers** — balanced low and mid-range reproduction
- Wide coverage: **90° × 60°** dispersion angle
- Frequency response **150Hz – 17kHz** (±3dB)
- Sensitivity **91 dB/W/m**, max SPL **100 dB**
- Compact design — **101×110×202mm**, only **3 kg**
- Ideal for **PA, announcement & conferencing** audio systems

The **Dekesi D-302YL** is a compact column speaker delivering 35W rated power with a dual 3-inch driver configuration. Designed for public address and announcement systems, it offers a wide 90°×60° dispersion angle and a frequency response of 150Hz–17kHz (±3dB), ensuring clear and well-distributed audio coverage. With a sensitivity of 91dB/W/m and a maximum SPL of 100dB, it balances performance and compactness. Weighing only 3kg and measuring 101×110×202mm, D-302YL is easy to install and reposition — making it an ideal choice for conference rooms, classrooms, retail spaces, and small-to-medium PA installations.

TECHNICAL SPECIFICATIONS

Model	D-302YL	Sensitivity	91 dB/W/m
Speaker Type	Column Speaker	Max SPL	100 dB
Rated Power	35W	Dispersion Angle	90° (H) × 60° (V)
Impedance	4Ω	Dimensions (W×D×H)	101 × 110 × 202 mm
Driver Configuration	2 × 3-inch	Weight	3 kg
Frequency Response	150Hz – 17kHz (±3dB)	Applications	PA, Announcement, Conference, Classroom